

Safe, effective scale prevention without the use of chemicals or salt.



Installation – check operating specifications before installing

1. KEEP THE UNIT IN AN UPRIGHT POSITION AT ALL TIMES.
2. Remove the red shipping caps from the inlet & outlet ports on the main housing.
3. **Precondition the unit by flushing:** It is very important that this system is flushed properly prior to final installation. Using the supplied adapter, connect a garden hose to the inlet port so that the water will flow into the system and out of the outlet port. Slowly turn on the water and allow the cloudy water to flow from the outlet into a bucket or drain. Flush the AST tanks for 5-10 minutes. Once the unit has been properly flushed, be sure the white washers are properly set inside the inlet and outlet ports. Disconnect it from the garden hose and position it for final installation.



4. Turn off main source water supply prior to installation.
5. Install the unit to the main water supply using the supplied components. Do not over tighten fittings, as this may cause leakage and broken fittings. **Do NOT use pipe dope.** The use of pipe dope voids the warranty. You may use NSF-certified pipe primer, glue and plumber's tape. Leave two-three threads exposed and do not exceed seven layers of plumber's tape. More than seven layers will cause the nipple to crack and leak.
6. **IMPORTANT:** The inlet piping assembly (valve, pre-filter, main filter unit, union and nipples) must be firmly braced and supported.
7. Once installation is complete, slowly turn the water on and inspect for leaks.
8. Once the unit is installed and checked for leaks, open the water faucet closest to the installed unit and allow water to run for 5-10 minutes for the final flushing period.

Contents



EQ-AST-WH –OR– EQ-AST-WH-C



These items included with standalone systems.



5-micron pre-filter unit
Model: EQ-PRE34PTW



Install kit:

- 1) filter housing wrench
- 2) ball type shut off valve
- 3) support bracket
- 4) 3/4"x3" nipples (4)
- 5) unions (2)
- 6) hose adaptor



Replace:
EQ-304
(4-pack)

All installation components included.

THIS UNIT MUST BE INSTALLED BY A LICENSED PLUMBER TO VALIDATE THE WARRANTY