



Chrome

Brushed Nickel

Oil-Rubbed Bronze



AQ-5300

- A AQ-5300 filter unit
- B Faucet (1)
- C Filter Cartridges (3)
- D Screws with anchors (2)
- E Faucet Rubber Washer (1)
- F Faucet Spacer (1)
- G Faucet Washer (1)
- H Faucet Nut (1)
- I 3"x1/4" Poly tubing (1)
- J Chrome nut (1)
- K Plastic collar (2)
- L Plastic tube insert (1)
- M 3"x3/4" Poly tubing (1)
- N Brass nut (1)
- O Brass tube insert (1)
- P 3/8" Brass Tee (1)



AQ-5200

- A AQ-5200 filter unit
- B Faucet (1)
- C Filter Cartridges (2)
- D Screws with anchors (2)
- E Faucet Rubber Washer (1)
- F Faucet Spacer (1)
- G Faucet Washer (1)
- H Faucet Nut (1)
- I 3"x1/4" Poly tubing (1)
- J Chrome nut (1)
- K Plastic collar (2)
- L Plastic tube insert (1)
- M 3"x1/4" Poly tubing (1)
- N Brass nut (1)
- O Brass tube insert (1)
- P 1/4" Brass Tee (1)



AQ-5100

- A AQ-5100 filter unit
- B Faucet (1)
- C Filter Cartridge (1)
- D Screws with anchors (2)
- E Faucet Rubber Washer (1)
- F Faucet Spacer (1)
- G Faucet Washer (1)
- H Faucet Nut (1)
- I 3"x1/4" Poly tubing (1)
- J Chrome nut (1)
- K Plastic collar (2)
- L Plastic tube insert (1)
- M 3"x1/4" Poly tubing (1)
- N Brass nut (1)
- O Brass tube insert (1)
- P 1/4" Brass Tee (1)

The AQ-5200 & 5300 comes in three designer finishes, Chrome, Brushed Nickel and Oil-Rubbed Bronze.

The AQ-5100 is only available with the Chrome finish.

The faucet may be mounted on the sink using an existing hole for a sprayer nozzle or soap dispenser, or by drilling a hole at least 1/2" in diameter. Be sure the location of the faucet allows the spout to extend slightly past the edge of the sink. Note: we recommend enlisting the services of an approved or certified professional if drilling is required.

Preparing for Installation

Please read entire installation guide before installing the filter system.

Tools Recommended for Installation

- Variable speed drill w/ 7/32" bit
- Adjustable wrench
- Measuring tape
- Bucket
- Phillips head screwdriver
- Hammer

Before beginning installation, please ensure all parts listed are present. If any part is missing or damaged, do not attempt to install the filter. Please contact Customer Service for replacement parts at (866) 662-6885.

Estimated Installation Time: 45 minutes